

TU-Chem Limited

Chemical Compounds for the Construction Industry

Forstrike

Concrete Mould Release Oil (BCA Category 2)

Description

High quality concrete mould oil for general site use that achieves a top quality finish.

Use

For use on all types of formwork in all climatic condition in general building construction.

Benefits

- Provides easy formwork release
- Provides high quality surface finish
- Minimizes form cleaning to reduce labour cost and extend formwork life
- Highly resistant to removal by rain or foot traffic
- Non-staining, suitable for use with coloured, white or standard OPC
- Will not impair the bond to concrete of any subsequent treatments
- Not classified as hazardous for transport

Application

- Prepare formwork, seal joints with formwork tape
- As near as possible to time of placement of concrete apply thinly by spray, brush or roller at a rate of up to 35 sq.mts per litre. BCA reports state that excessive application of concrete release agents is detrimental so avoid over-application.
- On porous forms such as untreated timber, for first usage only apply a double coat allowing time for maximum absorption before applying the second coat.
- On vertical forms remove any excess material accumulated at the bottom.

Colour: Amber

Coverage: 25 to 35 sq.mts.per litre depending upon surface texture and absorbency

Packaging: 210 litre drum, 25 litre bottle

Storage: Not affected by frost or ambient heat. No special consideration required.

Shelf Life: Unlimited in sealed containers when stored as recommended

