

Siteright Construction Supplies Ltd

19/21 Bridge Street
Bailey Gate Industrial Estate
Sturminster Marshall
Dorset BH21 4DB
Tel: 01258 858 028
Fax: 01258 858 064
Email: sales@siteright.net
Website: www.siteright.net

*Rapid site supply of a wide range of construction chemicals.
Suppliers of rebar, reinforcement mesh, construction
accessories and expansion joint products.*

Ecocure WW

Eco Concrete Curing Compound & Tinted Grade

Description

Environmentally friendly concrete curing membrane. A blue grade version is also available to help in identification during application.

Uses

- Locks in moisture into freshly cast concrete surfaces to prevent premature drying out.
- Reducing the risks of surface cracking and dusting
- The tinted version allows areas to be easily identified
- The dye breaks down on exposure to UV light and will not permanently discolour the concrete

Benefits

- Economical and easy to use
- Tinted grade available to assist identification during application
- Prevents premature drying out of the concrete surface reducing the risks of surface cracking and reducing the risk of surface dusting.
- Improves the durability of the concrete surface
- Silane compatible, guaranteed not to adversely affect the bond of subsequent coatings, screeds or renders

Application

For freshly cast surfaces: Apply as soon as final tamping or trowelling has been finished. If surface water is present a second application is desirable as soon as the surface water has evaporated. Make sure the correct rate is used to avoid ponding as it may glaze the surface of the concrete.

For surfaces struck from shuttering: Flood coat with water as soon as the formwork is struck, apply the chosen grade as soon as the water has run off. If this is not carried out it is possible that the curing compound will be “sucked” below the concrete surface leaving the surface unprotected. If the Tinted grade has been used UV light may not be able to act upon the “fugitive dye” thus leaving the concrete with a permanent colour. This advice is applicable whatever grade you may be using.

Note: Care should be taken that over spray does not get onto paint or glass as it may cause permanent damage if not rinsed off immediately.

Colour:	Light Blue
Coverage:	5-6 sq.mts per litre should be sufficient
Packaging:	210 litre drum, 25 litre bottle
Storage:	Store in dry, frost free conditions. Away from heat and direct sun light. Keep containers tightly closed
Shelf Life:	1 year in sealed container when stored as recommended.