

Siteright Construction Supplies Ltd

*Rapid site supply of a wide range of construction accessories.
Suppliers of rebar and reinforcement mesh.
Specialist site fabrications. Expansion joint products.*

19/21 Bridge Street
Bailey Gate Industrial Estate
Sturminster Marshall
Dorset BH21 4DB
Tel: 01258 858 028
Fax: 01258 858 064
Email: sales@siteright.net
Website: www.siteright.net

Ecotard MF

Environmentally friendly Mould & Form Face Retarder

Description

A transparent aqueous composition with a gel consistency colour tinted to assist application.

Uses

- To expose natural colour and texture of the coarse aggregate
- To produce a keyed surface for construction joints

Benefits

- Excellent non-slump properties for application to vertical surface
- Adheres well to treated surface after water carrier has evaporated
- Suitable for application to all types of mould and formwork surfaces

Application

- After long storage period lightly stir material to ensure uniform consistency.
- Ensure surface to be treated is clean, dry and free of any deposits.
- Apply uniformly by brush or roller at up to 4 sq.mts per litre.
- When placing concrete take precautions to ensure heavy scouring action does not remove the retarder.
- Removal of cement matrix should be as soon as possible after stripping and generally within 1-2 days after placing concrete. It should be carried out by low pressure water jetting and brooming or wire brushing in two directions at right angles to each other.

Colour: Blue

Coverage: 3-4 sq.mts per litre

Packaging: 25 litre bucket

Storage: Protect from frost. Keep containers sealed after use

Shelf Life: 1 year in sealed container when stored as recommended